



90.744.00..T000

SANIT WC element INEO PLUS disabled 1120/450



Item number	Product description
90.744.00..T000	<p>WC element INEO PLUS, handicapped accessible equipped with INEO FRESH box for water box cube, with small access opening, for wall-hung WC with mounting distance 180/230 mm, front-operated, h/w/d: 1,120/450/130 mm, WC mounted 50 mm higher than the standard height, for wall-hung WCs with an overhang > 60 cm, self-supporting powder-coated steel frame, for covering with plasterboard, installation onto a solid wall, in drywall constructions etc., 4-point-fastening, fully pre-assembled, includes self-locking feet with swivel base plates and fastening set, adjustment range of feet from unfinished floor level to upper edge of finished floor level: 0-200 mm, adjustment range front to wall: 135-205 mm (when mounted on wall brackets code no. 17.257.00..T000), with back-to-back installation distance between front edges 270-310 mm, with SANIT double bend, SANIT concealed cistern with insulation against condensation (CC-121-S-FO-2V-2C), with dual flush (7.5-4.5 l/ 4-2 l) and flexible cable technology, factory setting 6 and 3 litres, with protection cap for the flush pipe,</p> <p>SANIT fill valve Noise Class I, 2-part angle valve connection set R 1/2, 4-position adjustable mounting clip, WC connection bend 90° DN 90 (d:90) with reducing sleeve DN 90(d:90)/DN 100(d:110) with protection cap, SANIT complete WC connection set DN 90(d:90)/180 mm, protection box for access opening and ceramic fittings can be cut to size, flexible hose to fill valve, can be screwed by hand, 2 M12 WC retaining bolts, incl. templates for transferring the access openings to the cladding panel, mounting material, protection plug and installation instructions, packed in a box</p> <p>Concealed cistern tested to DIN EN 14055, Noise Class I</p> <p>The cleaning cubes being used must be suitable for WC plastic cisterns and must not contain chlorine or any oxidizing components, otherwise the cistern may be damaged (e.g. stress cracking).</p> <p>Accessories:</p> <ul style="list-style-type: none"> - fastenings (wall brackets, feet, bottom wall bracket) - WC flush actuators - sound-absorbing sets - WC connectors (double bend, offset connection bend, etc.) - cladding panel code no. 17.115.00..S000 - roughing-in set for shower toilet code no. 03.956.00..0000 - adjustable flush reducer code no. 05.261.00..0000